NSN 5306-01-480-6411

View Online at https://aerobasegroup.com/nsn/5306-01-480-6411

Shear Bolt - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.399 inches **Fastener Length:** Between 0.697 inches and 0.727 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.255 inches and 0.285 inches Width Between Flats: 0.251 inches **Extended Washer Diameter:** Between 0.340 inches and 0.350 inches **Extended Washer Thickness:** Between 0.054 inches and 0.074 inches **Hole Diameter:** Between 0.032 inches and 0.042 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **End Application:** F18 e/f **Thread Diameter:** 0.190 inches **Grip Length:** 0.313 inches **Hole Quantity:** 4 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Hole Configuration Style:** Double hexagon flats **Criticality Code Justification:** Agav **Product Name:** Bolt-colose tolerance, 12 point, flange head, 220 ksi ftu, cres

NSN 5306-01-480-6411

Shear Bolt - Page 2 of 2

A003b0



Material:
Steel comp xm-13
Material Specification:
Aams 5629 assn standard 15th material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Ams-qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: