

View Online at <https://aerobasegroup.com/nsn/5306-01-480-6412>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.389 inches

Fastener Length:

Between 0.624 inches and 0.654 inches

Head Style:

Spline extended washer

Head Height:

0.250 inches

Extended Washer Diameter:

Between 0.354 inches and 0.359 inches

Extended Washer Thickness:

Between 0.111 inches and 0.121 inches

Hole Diameter:

Between 0.070 inches and 0.075 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Head Minor Diameter:

Between 0.235 inches and 0.265 inches

End Application:

F18 e/f

Thread Diameter:

0.3750 inches

Grip Length:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Spline

Criticality Code Justification:

Agav

Product Name:

Bolt-close tolerance, spline drive, flange head (220 ksi ftu)cres

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0