NSN 5306-01-480-8291

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-480-8291
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
Between 0.892 inches and 0.922 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
End Application:
F18 e/f
Thread Diameter:
0.3125 inches
Grip Length:
Between 0.418 inches and 0.448 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Criticality Code Justification:
Agav
Product Name:
Bolt, hex head, close tolerance, a286 cres, long threads, self-locking and nonlocking
Material:
Iron alloy 660
Material Specification:
As-5731 assn standard 1st material response, or ams5732 assn standard 2nd material response, or ams5737 assn standard 3rd material

As-5731 assn standard 1st material response or ams5732 assn standard 2nd material response or ams573 response or ams5853 assn standard 4th material response

NSN 5306-01-480-8291

Shear Bolt - Page 2 of 2

A003b0



Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, tyoe ii, class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: