

View Online at <https://aerobasegroup.com/nsn/5306-01-480-8292>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.399 inches

**Fastener Length:**

Between 0.574 inches and 0.604 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.255 inches and 0.285 inches

**Width Between Flats:**

0.251 inches

**Extended Washer Diameter:**

Between 0.340 inches and 0.350 inches

**Extended Washer Thickness:**

Between 0.054 inches and 0.074 inches

**Hole Diameter:**

Between 0.032 inches and 0.042 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**End Application:**

F18 e/f

**Thread Diameter:**

0.190 inches

**Grip Length:**

0.250 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Hole Configuration Style:**

Double hexagon flats

**Criticality Code Justification:**

Agav

**Product Name:**

Bolt-close-tolerance, 12 point, flange head, 220 ksi ftu, cres

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams-qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0