

View Online at <https://aerobasegroup.com/nsn/5306-01-480-8320>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.399 inches

Fastener Length:

Between 0.759 inches and 0.789 inches

Head Style:

Spline extended washer

Head Height:

Between 0.265 inches and 0.285 inches

Extended Washer Diameter:

Between 0.340 inches and 0.350 inches

Extended Washer Thickness:

Between 0.054 inches and 0.074 inches

Hole Diameter:

Between 0.032 inches and 0.042 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Head Minor Diameter:

0.278 inches

End Application:

F18 e/f

Thread Diameter:

0.190 inches

Grip Length:

0.375 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Product Name:

Bolt-close tolerance, 12 point, flange head, 220 ksi ftu, cres

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0