

View Online at <https://aerobasegroup.com/nsn/5306-01-480-9926>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.589 inches

Fastener Length:

Between 0.849 inches and 0.879 inches

Head Style:

Spline extended washer

Head Height:

Between 0.302 inches and 0.322 inches

Extended Washer Diameter:

Between 0.575 inches and 0.585 inches

Extended Washer Thickness:

Between 0.035 inches and 0.055 inches

Hole Diameter:

Between 0.060 inches and 0.070 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Head Minor Diameter:

Between 0.360 inches and 0.375 inches

End Application:

F18 e/f

Thread Diameter:

0.3125 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

220000 pounds per square inch

Hole Configuration Style:

Spline

Criticality Code Justification:

Agav

Surface Finish:

32.0 microinches grip

Product Name:

Bolt, ktension: nickel alloy 718: 220 ksi ftu: external wrenching, spline drive, flanged head

Special Features:

Passivations with dry film lube

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard 1st material response or ams 5663 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0