

View Online at <https://aerobasegroup.com/nsn/5306-01-481-0024>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.614 inches

**Fastener Length:**

Between 3.474 inches and 3.504 inches

**Head Style:**

Spline extended washer

**Head Height:**

0.337 inches

**Extended Washer Diameter:**

Between 0.691 inches and 0.701 inches

**Extended Washer Thickness:**

0.054 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Head Minor Diameter:**

Between 0.438 inches and 0.453 inches

**End Application:**

F18 e/f

**Thread Diameter:**

0.3750 inches

**Grip Length:**

2.875 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Product Name:**

Bolt-close tolerance, spline drive, fland head (220 ksi ft

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams-qq-p-35 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0