

View Online at <https://aerobasegroup.com/nsn/5306-01-482-2246>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.370 inches

**Fastener Length:**

1.620 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.429 inches and 0.439 inches

**Grip Diameter:**

Between 0.248 inches and 0.249 inches

**Thread Diameter:**

0.250 inches

**Grip Length:**

1.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Steel comp 4340 fastener or steel comp 8740 fastener

**Material Specification:**

Ams6415 assn standard 1st material response fastener or ams6322 assn standard 2nd material response fastener or mil-s-6049 military specification 2nd material response fastener

**Surface Treatment:**

Cadmium bearing surface of head

**Surface Treatment Specification:**

Qq-p-416, ty11, cl2 federal specification single treatment response bearing surface of head

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.