

View Online at <https://aerobasegroup.com/nsn/5306-01-482-2899>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.498 inches

Fastener Length:

1.383 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.553 inches and 0.565 inches

Shoulder Diameter:

0.371 inches first shoulder and 0.374 inches first shoulder

Shoulder Length:

0.885 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.202 inches

Shoulder Shape:

Round first shoulder

Material:

Steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 or steel comp 4140

Material Specification:

Mil-s-6050 military specification 1st material response or mil-s-6098 military specification 2nd material response or mils-6758 military specification 3rd material response or ams6300 assn standard 4th material response or mil-s-5626 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl 1 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.