## NSN 5306-01-482-4274

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-482-4274 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.659 inches **Fastener Length:** Between 2.886 inches and 2.906 inches **Head Style:** Spline extended washer **Head Height:** Between 0.327 inches and 0.347 inches **Extended Washer Diameter:** Between 0.691 inches and 0.701 inches **Extended Washer Thickness:** Between 0.044 inches and 0.064 inches **Grip Diameter:** Between 0.374 inches and 0.375 inches **Head Minor Diameter:** Between 0.423 inches and 0.438 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.865 inches and 1.885 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 24700 pounds per square inch Material: Nickel alloy 718 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5306-01-482-4274

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

spec.