## NSN 5306-01-483-3653

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-483-3653



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.874 inches and 0.934 inches

## Fastener Length:

1.312 inches

#### **Head Style:**

Double hexagon w/hole

#### **Head Height:**

0.348 inches

## Width Between Flats:

0.375 inches

#### Extended Washer Diameter:

## 0.500 inches

## **Extended Washer Thickness:**

0.070 inches

## Grip Diameter:

Between 0.280 inches and 0.290 inches

## **End Application:**

1055-01-450-4243

## Thread Diameter:

0.312 inches

## Grip Length:

Between 0.378 inches and 0.438 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

130000 pounds per square inch

## Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

## Minimum Yield Strength:

85000 pounds per square inch

## Material:

Iron alloy 660

## **Material Specification:**

Ams 5731-85 assn standard single material response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

# NSN 5306-01-483-3653

Machine Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

