

View Online at <https://aerobasegroup.com/nsn/5306-01-485-0495>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.990 inches and 1.070 inches

Fastener Length:

Between 2.400 inches and 2.600 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.412 inches and 0.432 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.552 inches and 0.572 inches

Extended Washer Thickness:

Between 0.090 inches and 0.100 inches

End Application:

Direct vendor delivery (dvd), model xm1117, armored security vehicle (asv), nsn 2320-01-437-6957, cage 10237, part number 216098, tm 9-2320-307-24p, contract daae07-99-c-s001

Thread Diameter:

0.375 inches

Grip Length:

Between 0.252 inches and 0.312 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Surface Finish:

63.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams5732 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0