NSN 5306-01-485-0733

Shear Bolt - Page 1 of 2



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** 0.500 inches Fastener Length: Between 0.615 inches and 0.635 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.225 inches and 0.245 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.465 inches and 0.475 inches **Extended Washer Thickness:** Between 0.032 inches and 0.052 inches Hole Diameter: Between 0.036 inches and 0.042 inches **Grip Diameter:** Between 0.2481 inches and 0.2495 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.115 inches and 0.135 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hole Configuration Style: Double hexagon flats Color: Black threads Material: Nickel alloy 718 **Material Specification:**

Ams5662 assn standard single material response or ams5962 assn standard single material response



NSN 5306-01-485-0733

Shear Bolt - Page 2 of 2



Surface Treatment:

Aluminum

Surface Treatment Specification:

Bms10-85 cage 81205 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0