

View Online at <https://aerobasegroup.com/nsn/5306-01-486-3593>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.852 inches

Fastener Length:

Between 0.552 inches and 0.572 inches

Head Style:

Double hexagon extended washer

Head Height:

0.557 inches

Width Between Flats:

0.625 inches

Extended Washer Diameter:

Between 0.928 inches and 0.938 inches

Extended Washer Thickness:

Between 0.610 inches and 0.625 inches

Grip Diameter:

Between 0.5605 inches and 0.5615 inches

Thread Diameter:

0.5625 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

200000 pounds per square inch

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740 or steel comp 6150

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-8503 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.