

View Online at <https://aerobasegroup.com/nsn/5306-01-486-3653>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.614 inches

**Fastener Length:**

1.677 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.378 inches and 0.398 inches

**Width Between Flats:**

Between 0.429 inches and 0.449 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

Between 0.081 inches and 0.101 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches and 0.111 inches first hole

**End Application:**

F-15

**Thread Diameter:**

0.375 inches

**Grip Length:**

1.063 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Criticality Code Justification:**

Feat

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.188 inches and 1.228 inches first hole

**Special Features:**

Item is not csi but has critical features such as heat treatment, surface finish, or material type and special insp. Req.S such as magnetic particle insp. Or fluorescent penetrant inspection

**Material:**

Steel comp 8660h

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0