## NSN 5306-01-487-2922

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-487-2922 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** 0.688 inches **Head Style:** Dished hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.104 inches first hole and 0.119 inches first hole **Thread Diameter:** 0.312 inches **Grip Length:** 0.250 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 0.506 inches first hole Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5306-01-487-2922

Shear Bolt - Page 2 of 2



Fiig:

A003b0