NSN 5306-01-488-2232

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-488-2232

Thread Class:

| 3a |
|--|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.300 inches and 0.409 inches |
| Fastener Length: |
| Between 1.549 inches and 1.559 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.110 inches and 0.125 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Shoulder Diameter: |
| 0.249 inches |
| Shoulder Length: |
| 1.187 inches and 1.197 inches |
| End Application: |
| F/a-22 raptor |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 2350 pounds per square inch |
| Shoulder Shape: |
| Round |
| Product Name: |
| Bolt |
| Material: |
| Stainless steel |
| Material Specification: |
| Ams 5731 assn standard 1st material response or ams 5737 assn standard 2nd material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205 - nas 1160 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5306-01-488-2232

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0