

View Online at <https://aerobasegroup.com/nsn/5306-01-488-8001>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.528 inches

**Fastener Length:**

3.340 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.250 inches and 0.265 inches

**Width Between Flats:**

Between 0.741 inches and 0.752 inches

**Grip Diameter:**

Between 0.4985 inches and 0.4995 inches

**End Application:**

E-3a

**Thread Diameter:**

0.500 inches

**Grip Length:**

2.812 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Material Specification:**

Ams6349 assn standard 1st material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response or ams6322 assn standard 3rd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.