NSN 5306-01-489-5922

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-489-5922

3a
Thread Direction:
Right-hand
Thread Length:
0.589 inches
Fastener Length:
Between 1.349 inches and 1.379 inches
Head Style:
Spline extended washer
Head Height:
Between 0.302 inches and 0.322 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
Between 0.035 inches and 0.055 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Head Minor Diameter:
Between 0.360 inches and 0.375 inches
End Application:
F-22
Thread Diameter:
0.313 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Special Features:
Dry film lubricant per mil-l-46010, type i
Material:
Nickel alloy 718
Material Specification:
Ams5662j assn standard 1st material response or ams5663 assn standard 2nd material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unif

NSN 5306-01-489-5922

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0