

View Online at <https://aerobasegroup.com/nsn/5306-01-489-5922>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.589 inches

**Fastener Length:**

Between 1.349 inches and 1.379 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.302 inches and 0.322 inches

**Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

**Extended Washer Thickness:**

Between 0.035 inches and 0.055 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Head Minor Diameter:**

Between 0.360 inches and 0.375 inches

**End Application:**

F-22

**Thread Diameter:**

0.313 inches

**Grip Length:**

Between 0.740 inches and 0.760 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Special Features:**

Dry film lubricant per mil-I-46010, type i

**Material:**

Nickel alloy 718

**Material Specification:**

Ams5662j assn standard 1st material response or ams5663 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0