NSN 5306-01-490-1726

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-490-1726 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.589 inches **Fastener Length:** Between 1.662 inches and 1.692 inches **Head Style:** Spline extended washer **Head Height:** Between 0.302 inches and 0.322 inches **Extended Washer Diameter:** Between 0.575 inches and 0.585 inches **Extended Washer Thickness:** Between 0.035 inches and 0.055 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Head Minor Diameter:** Between 0.360 inches and 0.375 inches **End Application:** F-22 **Thread Diameter:** 0.313 inches **Grip Length:** Between 1.053 inches and 1.073 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Special Features:** Dry film lubricant per mil-l-46010, type i Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard 1st material response or ams5663 assn standard 2nd material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-490-1726

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0