NSN 5306-01-492-4899



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-492-4899 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.016 inches and 1.066 inches **Fastener Length:** Between 6.151 inches and 6.181 inches **Head Style:** Dished hexagon **Head Height:** Between 0.375 inches and 0.390 inches Width Between Flats: Between 1.052 inches and 1.065 inches **Grip Diameter:** Between 0.7480 inches and 0.7490 inches **End Application:** F-22 **Thread Diameter:** 0.750 inches **Grip Length:** Between 5.115 inches and 5.135 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response

N/a

Shelf Life:

Unjf

Thread Series Designator:

NSN 5306-01-492-4899

Shear Bolt - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.