

View Online at <https://aerobasegroup.com/nsn/5306-01-495-1094>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.338 inches

Fastener Length:

Between 0.4325 inches and 0.4525 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.339 inches and 0.381 inches

Hole Diameter:

Between 0.070 inches and 0.080 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Thread Diameter:

0.190 inches

Grip Length:

Between 0.1775 inches and 0.1975 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Round

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Bolt, 100 degrees flush head 160, 000 psi uts

Material:

Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification single material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-60494 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.