

View Online at <https://aerobasegroup.com/nsn/5306-01-495-2698>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.920 inches and 1.997 inches

**Fastener Length:**

Between 1.890 inches and 1.937 inches

**Head Style:**

Hexagon

**Head Height:**

0.172 inches

**Width Between Flats:**

Between 0.365 inches and 0.377 inches

**Hole Diameter:**

Between 0.070 inches and 0.080 inches

**Grip Diameter:**

Between 0.167 inches and 0.190 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches all holes and 0.080 inches all holes

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.030 inches and 0.060 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

32

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.940 inches all holes and 0.950 inches all holes

**Product Name:**

Bolt-full threaded, 160 ksi steel, drilled head

**Material:**

Stainless steel

**Material Specification:**

Ams 5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0