## NSN 5306-01-495-2698

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-495-2698

| View Online at https://aerobasegroup.com/nsn/5306-01-495-2698    |  |  |  |
|--|--|--|--|
| Thread Class:  |  |  |  |
| 3a   |  |  |  |
| Thread Direction:  |  |  |  |
| Right-hand   |  |  |  |
| Thread Length:   |  |  |  |
| Between 1.920 inches and 1.997 inches                            |  |  |  |
| Fastener Length:   |  |  |  |
| Between 1.890 inches and 1.937 inches                            |  |  |  |
| Head Style:  |  |  |  |
| Hexagon  |  |  |  |
| Head Height:   |  |  |  |
| 0.172 inches   |  |  |  |
| Width Between Flats:   |  |  |  |
| Between 0.365 inches and 0.377 inches                            |  |  |  |
| Hole Diameter:   |  |  |  |
| Between 0.070 inches and 0.080 inches                            |  |  |  |
| Grip Diameter:   |  |  |  |
| Between 0.167 inches and 0.190 inches                            |  |  |  |
| Shank Unthreaded Hole Diameter:                                  |  |  |  |
| 0.070 inches all holes and 0.080 inches all holes                |  |  |  |
| Thread Diameter:   |  |  |  |
| 0.190 inches   |  |  |  |
| Grip Length:   |  |  |  |
| Between 0.030 inches and 0.060 inches                            |  |  |  |
| Hole Quantity:   |  |  |  |
| 3  |  |  |  |
| Hole Type:   |  |  |  |
| Drilled  |  |  |  |
| Thready Qty Per Inch (tpi):                                      |  |  |  |
| 32   |  |  |  |
| Hole Configuration Style:  |  |  |  |
| Hexagon flats  |  |  |  |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |  |  |  |
| 0.940 inches all holes and 0.950 inches all holes                |  |  |  |
| Product Name:  |  |  |  |
| Bolt-full threaded, 160 ksi steel, drilled head                  |  |  |  |
| Material:  |  |  |  |
| Stainless steel  |  |  |  |
| Material Specification:  |  |  |  |
| Ams 5737 assn standard single material response                  |  |  |  |
| Surface Treatment:   |  |  |  |
| Passivate  |  |  |  |

Passivate

## NSN 5306-01-495-2698

Machine Bolt - Page 2 of 2



| Surface | <b>Treatment</b> | Specification: |
|---------|------------------|----------------|
|---------|------------------|----------------|

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0