## NSN 5306-01-495-2698

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-495-2698

View Online at https://aerobasegroup.com/nsn/5306-01-495-2698			
Thread Class:			
3a			
Thread Direction:			
Right-hand			
Thread Length:			
Between 1.920 inches and 1.997 inches			
Fastener Length:			
Between 1.890 inches and 1.937 inches			
Head Style:			
Hexagon			
Head Height:			
0.172 inches			
Width Between Flats:			
Between 0.365 inches and 0.377 inches			
Hole Diameter:			
Between 0.070 inches and 0.080 inches			
Grip Diameter:			
Between 0.167 inches and 0.190 inches			
Shank Unthreaded Hole Diameter:			
0.070 inches all holes and 0.080 inches all holes			
Thread Diameter:			
0.190 inches			
Grip Length:			
Between 0.030 inches and 0.060 inches			
Hole Quantity:			
3			
Hole Type:			
Drilled			
Thready Qty Per Inch (tpi):			
32			
Hole Configuration Style:			
Hexagon flats			
Distance From Head Largest Bearing Surface To Shank Hole Center:			
0.940 inches all holes and 0.950 inches all holes			
Product Name:			
Bolt-full threaded, 160 ksi steel, drilled head			
Material:			
Stainless steel			
Material Specification:			
Ams 5737 assn standard single material response			
Surface Treatment:			
Passivate			

Passivate

## NSN 5306-01-495-2698

Machine Bolt - Page 2 of 2



Surface	<b>Treatment</b>	Specification:
---------	------------------	----------------

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0