

View Online at <https://aerobasegroup.com/nsn/5306-01-497-1789>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.498 inches

Fastener Length:

Between 1.560 inches and 1.600 inches

Head Style:

Hexagon

Head Height:

Between 0.203 inches and 0.235 inches

Width Between Flats:

Between 0.553 inches and 0.565 inches

Shoulder Diameter:

0.371 inches first shoulder and 0.374 inches first shoulder

Shoulder Length:

1.072 inches first shoulder and 1.092 inches first shoulder

Hole Diameter:

0.070 inches

Thread Diameter:

0.312 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Hexagon flats

Shoulder Shape:

Round first shoulder

Material:

Steel comp 4037 or steel comp 8630 or steel comp 8740 or steel comp 4140 or steel comp 4130

Material Specification:

Ams6300 assn standard 1st material response or ams6280 assn standard 2nd material response or mil-s-605 military specification 2nd material response or ams6322 assn standard 3rd material response or mil-s-6049 military specification 3rd material response or ams6382 assn standard 4th material response or mil-s-6758 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, tyii, cl1 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-605 spec.