## NSN 5306-01-498-6744

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-498-6744

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
Between 2.516 inches and 2.546 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Grip Diameter:
Between 0.311 inches and 0.312 inches
Single Shear Strength:
95000 pounds per square inch
End Application:
F/a-22 raptor
Thread Diameter:
0.312 inches
Grip Length:
Between 2.052 inches and 2.072 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Bolt, hex head
Material:
Iron alloy 660
Material Specification:
Ams 5731 national std/spec 1st material response or ams 5737 national std/spec 2nd material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 national std/spec single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205 - nas 6705 professional/industrial association standard

## NSN 5306-01-498-6744

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

