NSN 5306-01-499-1965

Close Tolerance Bolt - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-01-499-1965

| View Online at https://aerobasegroup.com/nsn/5306-01-499-1965 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.284 inches and 0.362 inches |
| Fastener Length: |
| Between 0.433 inches and 0.463 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| 0.381 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Point Diameter: |
| Between 0.181 inches and 0.184 inches |
| Point Style: |
| Flat |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.084 inches and 0.159 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Aluminum alloy |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type ii, class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |