## NSN 5306-01-499-1990

Shear Bolt - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5306-01-499-1990 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.408 inches **Fastener Length:** Between 1.356 inches and 1.386 inches **Head Style:** Spline extended washer **Head Height:** Between 0.195 inches and 0.215 inches **Extended Washer Diameter:** Between 0.349 inches and 0.359 inches **Extended Washer Thickness:** Between 0.017 inches and 0.037 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Head Minor Diameter:** Between 0.173 inches and 0.188 inches **End Application:** F-22 **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.848 inches and 0.928 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 22000 pounds per square inch **Product Name:** Bolt, tension, nickel alloy 718, 220ksi ftu, external wrenching, spline drive, flanged head **Special Features:** Dry film lubricant per mil-l-46010, type i Material: Nickel alloy 718 **Material Specification:** Ams5662 assn standard single material response or ams5663 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

## NSN 5306-01-499-1990

Shear Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0