

View Online at <https://aerobasegroup.com/nsn/5306-01-499-6558>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.291 inches and 0.362 inches

**Fastener Length:**

Between 1.424 inches and 1.434 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.110 inches and 0.125 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Shoulder Diameter:**

0.2490 inches first shoulder and 0.2495 inches first shoulder

**Shoulder Length:**

1.062 inches first shoulder and 1.072 inches first shoulder

**End Application:**

F-22

**Thread Diameter:**

0.1900 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

2350 pounds per square inch

**Shoulder Shape:**

Round

**Product Name:**

Bolt, shoulder, hex head, close tolerance, cres-a286

**Material:**

Stainless steel

**Material Specification:**

Ams 5731 assn standard 1st material response or ams 5737 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type ii or viii federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0