NSN 5306-01-499-6558

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-499-6558 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.362 inches **Fastener Length:** Between 1.424 inches and 1.434 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Shoulder Diameter:** 0.2490 inches first shoulder and 0.2495 inches first shoulder **Shoulder Length:** 1.062 inches first shoulder and 1.072 inches first shoulder **End Application:** F-22 **Thread Diameter:** 0.1900 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2350 pounds per square inch **Shoulder Shape:** Round **Product Name:** Bolt, shoulder, hex head, close tolerance, cres-a286 Material: Stainless steel **Material Specification:** Ams 5731 assn standard 1st material response or ams 5737 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type ii or viii federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

NSN 5306-01-499-6558

Shoulder Bolt - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0