## NSN 5306-01-500-0497

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-500-0497 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.535 inches and 1.565 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.506 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.2500 inches **Grip Length:** Between 1.115 inches and 1.135 inches **Hole Quantity:** Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degrees flush head Material: Steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification single material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification 3rd material response or mil-s-6049 military specification 4th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty ii, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5306-01-500-0497

Shear Bolt - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.