## NSN 5306-01-500-2265

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-500-2265 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.498 inches **Fastener Length:** Between 3.986 inches and 4.026 inches **Head Style:** Hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Shoulder Diameter:** 0.250 inches first shoulder **Shoulder Length:** 3.020 inches first shoulder **End Application:** F-22 **Thread Diameter:** 0.3125 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 7490 pounds per square inch **Shoulder Shape:** Round **Product Name:** Bolt, shoulder, hex head, close tolerance, cres-a286 Material: Stainless steel **Material Specification:** Ams5731 assn standard 1st material response or ams5737 assn standard 2nd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, type ii or viii federal specification 1st treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## **NSN 5306-01-500-2265** Shoulder Bolt - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

Demilitarization:

No

Fiig:

A003b0