NSN 5306-01-500-4205



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-500-4205 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.702 inches **Fastener Length:** Between 1.811 inches and 1.843 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.378 inches and 0.398 inches Width Between Flats: 0.4375 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** Between 0.081 inches and 0.101 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **End Application:** Fleet combat **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.125 inches and 1.135 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Material: Steel comp 4340 **Material Specification:** Mil-s-8844; class 1 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Ams2401-3 assn standard 1st treatment response and qq-p-416; type 2 federal specification 2nd treatment response

Unjf

Shelf Life:

Thread Series Designator:

N/a

NSN 5306-01-500-4205

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8844 spec.