

View Online at <https://aerobasegroup.com/nsn/5306-01-500-4205>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.702 inches

Fastener Length:

Between 1.811 inches and 1.843 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

0.4375 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

End Application:

Fleet combat

Thread Diameter:

0.375 inches

Grip Length:

Between 1.125 inches and 1.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Material:

Steel comp 4340

Material Specification:

Mil-s-8844; class 1 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Ams2401-3 assn standard 1st treatment response and qq-p-416; type 2 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-8844 spec.