NSN 5306-01-500-6306 Machine Bolt - Page 1 of 2



| Machine Bolt - Page 1 of 2 |
|--|
| View Online at https://aerobasegroup.com/nsn/5306-01-500-6306 |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 9.4 millimeters |
| Fastener Length: |
| Between 14.20 millimeters and 14.24 millimeters |
| Head Style: |
| Fillister countersunk |
| Head Diameter: |
| Between 10.79 millimeters and 10.93 millimeters |
| Head Height: |
| 0.38 millimeters |
| Grip Diameter: |
| Between 4.84 millimeters and 4.90 millimeters |
| Thread Diameter: |
| 5.0 millimeters |
| Grip Length: |
| 7.0 millimeters |
| Thread Pitch In Millimeters: |
| 0.8 |
| External Thread Tolerance Class: |
| 4h |
| Countersink Angle: |
| 100.0 degrees |
| Color: |
| Blue |
| Material: |
| Titanium alloy uns r54520 |
| Material Specification: |
| Ams4028 assn standard single material response or ams4967 assn standard single material response |
| Surface Treatment: |
| Aluminum |
| Surface Treatment Specification: |
| Hi-shear specification 294 mfr ref single treatment response |
| Thread Series Designator: |

Μ

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5306-01-500-6306 Machine Bolt - Page 2 of 2

Fiig: A003b0

