NSN 5306-01-500-7825

Shear Bolt - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5306-01-500-7825

| Thread Class. | |
|--|---------------------------|
| Thread Class: | |
| 3a Thread Direction | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.370 inches | |
| Fastener Length: | |
| Between 0.605 inches and 0.635 inches | |
| Head Style: | |
| Dished hexagon | |
| Head Height: | |
| Between 0.125 inches and 0.140 inches | |
| Width Between Flats: | |
| Between 0.429 inches and 0.439 inches | |
| Locking Feature: | |
| Patch threads | |
| Grip Diameter: | |
| Between 0.2490 inches and 0.2495 inches | |
| Thread Diameter: | |
| 0.250 inches | |
| Grip Length: | |
| Between 0.240 inches and 0.260 inches | |
| Thready Qty Per Inch (tpi): | |
| 28 | |
| Min. Tensile Strength (psi): | |
| 160000 pounds per square inch | |
| Surface Finish: | |
| 32.0 microinches threads | |
| Material: | |
| Titanium alloy uns r56400 fastener | |
| Material Specification: | |
| Ams4928 assn standard single material response fastener or ams4967 assn standard single ma | aterial response fastener |
| Thread Series Designator: | |
| Unjf | |
| Specification Data: | |
| 80205-nas6404 professional/industrial association standard | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| | |

NSN 5306-01-500-7825

Shear Bolt - Page 2 of 2

Fiig: A003b0

