

View Online at <https://aerobasegroup.com/nsn/5306-01-501-5860>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.360 inches

Fastener Length:

1.172 inches

Head Style:

Hexagon

Head Height:

0.188 inches

Width Between Flats:

0.562 inches

Grip Diameter:

0.374 inches

Thread Diameter:

0.375 inches

Grip Length:

0.813 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 8740 or steel comp 4140 or steel comp 4340 or steel comp e4340 or steel comp 8735 or steel comp 6150

Material Specification:

Ams6322 assn standard 1st material response or mil-s-6049 military specification 1st material response or ams6382 assn standard 2nd material response or mil-s-5626 military specification 2nd material response or ams6415 assn standard 3rd material response or mil-s-500 military specification 4th material response or mil-s-6098 military specification 5th material response or mil-s-8503 military specification 6th material response

Surface Treatment:

Cadmium head

Surface Treatment Specification:

Qq-p-416, tyii, cl2 federal specification single treatment response head

Thread Series Designator:

Unjf

Specification Data:

80205-nas464 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.