## NSN 5306-01-502-9291

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-502-9291 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.530 inches **Fastener Length:** Between 1.1566 inches and 1.1587 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.4689 inches and 0.4739 inches **Head Height:** Between 0.0593 inches and 0.0614 inches **Grip Diameter:** Between 0.302 inches and 0.306 inches **Thread Diameter:** 0.3125 inches **Grip Length:** 0.688 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 5000 pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel **Material Specification:** Mil-s-500 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5306-01-502-9291

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-500 spec.