

View Online at <https://aerobasegroup.com/nsn/5306-01-503-0966>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.575 inches

**Fastener Length:**

Between 1.998 inches and 2.028 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.302 inches and 0.322 inches

**Extended Washer Diameter:**

Between 0.575 inches and 0.585 inches

**Extended Washer Thickness:**

Between 0.035 inches and 0.055 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Head Minor Diameter:**

Between 0.360 inches and 0.375 inches

**End Application:**

C-17 aircraft

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.428 inches and 1.448 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Surface Finish:**

32.0 microinches grip

**Product Name:**

Bolt, tension, spline drive-inconel 718, 220-255 ksi ftu

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0