NSN 5306-01-503-1666

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-503-1666

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.645 inches
Fastener Length:
Between 2.068 inches and 2.098 inches
Head Style:
Spline extended washer
Head Height:
Between 0.327 inches and 0.347 inches
Extended Washer Diameter:
Between 0.691 inches and 0.701 inches
Extended Washer Thickness:
Between 0.044 inches and 0.064 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Head Minor Diameter:
Between 0.423 inches and 0.438 inches
End Application:
C-17a aircraft
Thread Diameter:
0.375 inches
Grip Length:
Between 1.428 inches and 1.448 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Surface Finish:
32.0 microinches grip
Product Name:
Bolt, tension, spline drive-inconel 718, 220-255 ksi ftu
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

NSN 5306-01-503-1666

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0