NSN 5306-01-505-1160

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-505-1160

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.528 inches
Fastener Length:
Between 2.888 inches and 2.918 inches
Head Style:
Dished hexagon
Head Height:
Between 0.250 inches and 0.265 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Grip Diameter:
Between 0.514 inches and 0.515 inches
End Application:
Kc-135 aircraft
Thread Diameter:
0.500 inches
Grip Length:
Between 2.365 inches and 2.385 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Thread Series Designator:
Unif
Specification Data:
80205-nas6208 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5306-01-505-1160

Shear Bolt - Page 2 of 2



em			

No

Fiig:

A003b0