NSN 5306-01-505-1176

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-505-1176 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.460 inches and 0.487 inches **Fastener Length:** Between 2.450 inches and 2.497 inches **Head Style:** Double hexagon **Head Height:** Between 0.247 inches and 0.267 inches Width Between Flats: Between 0.678 inches and 0.689 inches **Grip Diameter:** Between 0.4358 inches and 0.4367 inches **End Application:** A-10 thunderbolt ii acft **Thread Diameter:** 0.437 inches **Grip Length:** Between 1.990 inches and 2.010 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Surface Finish:** 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:**

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-505-1176

Shear Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0