

View Online at <https://aerobasegroup.com/nsn/5306-01-505-1217>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.528 inches

Fastener Length:

Between 3.325 inches and 3.355 inches

Head Style:

Dished hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Grip Diameter:

Between 0.514 inches and 0.515 inches

End Application:

Kc-135

Thread Diameter:

0.500 inches

Grip Length:

Between 2.802 inches and 2.822 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Ams6349 assn standard 1st material response or ams6484 assn standard 1st material response or ams6415 assn standard 1st material response or ams6322 assn standard 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Cadmium and chromium

Thread Series Designator:

Unjf

Specification Data:

80205-nas6208 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.