NSN 5306-01-505-2380

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-505-2380

view Online at https://derobasegroup.com/nsi//3500-01-503-2500
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.594 inches
Fastener Length:
Between 1.079 inches and 1.109 inches
Head Style:
Hexagon
Head Height:
Between 0.281 inches and 0.296 inches
Width Between Flats:
Between 0.865 inches and 0.877 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Grip Diameter:
Between 0.5605 inches and 0.5815 inches
End Application:
Adapter
Thread Diameter:
0.5625 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
1600 pounds per square inch
Material:
Steel comp 4340
Material Specification:
Nas4002 national specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, typeii, class 2 federal specification single treatment response
Thread Series Designator:
Unf
Specification Data:
80205-nas6209 professional/industrial association standard

N/a

NSN 5306-01-505-2380

Shear Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0