NSN 5306-01-505-2677

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-505-2677 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.184 inches **Fastener Length:** Between 4.194 inches and 4.224 inches **Head Style:** Dished hexagon **Head Height:** Between 0.438 inches and 0.453 inches Width Between Flats: Between 1.239 inches and 1.252 inches **Grip Diameter:** Between 0.8886 inches and 0.8896 inches **End Application:** C-135 stratolifter **Thread Diameter:** 0.875 inches **Grip Length:** Between 3.115 inches and 3.135 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 ty ii, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5306-01-505-2677

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.