## NSN 5306-01-505-3449

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-505-3449 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 1.8750 inches and 1.9050 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.3891 inches and 0.3901 inches **End Application:** C-135 stratolifter **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.3020 inches and 1.3220 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch

Material:

Steel comp e4340 or steel comp 8740

**Material Specification:** 

Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response

**Surface Treatment:** 

Cadmium

**Surface Treatment Specification:** 

Qq-p-416 ty ii, cl 2 federal specification all treatment responses

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

## NSN 5306-01-505-3449

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.