## NSN 5306-01-505-3453

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-505-3453

Thread	Class:
i ili caa	01035.

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.578 inches

#### Fastener Length:

Between 1.8750 inches and 1.9050 inches

#### **Head Style:**

Dished hexagon

#### Head Height:

Between 0.188 inches and 0.203 inches

## Width Between Flats:

Between 0.554 inches and 0.564 inches

#### Grip Diameter:

Between 0.4047 inches and 0.4057 inches

#### **End Application:**

C-135 stratolifter

#### **Thread Diameter:**

0.375 inches

## Grip Length:

Between 1.3020 inches and 1.3220 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Material:

Steel comp e4340 or steel comp 8740

## Material Specification:

Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response

## Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416 ty ii, cl 2 federal specification all treatment responses

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5306-01-505-3453

Shear Bolt - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-s-6049 spec.

