## NSN 5306-01-505-3631

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-505-3631 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.6940 inches **Fastener Length:** Between 2.0540 inches and 2.0840 inches **Head Style:** Dished hexagon **Head Height:** Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.678 inches and 0.690 inches **Grip Diameter:** Between 0.4516 inches and 0.4526 inches **End Application:** C-135 stratolifter **Thread Diameter:** 0.4375 inches **Grip Length:** Between 1.3650 inches and 1.3850 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-6049 military specification 1st material response or ams6322 assn standard 2nd material response or ams6484 assn standard 2nd material response or ams6415 assn standard 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 ty ii, cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life:

Demilitarization: No

**Unit Of Measure:** 

N/a

## NSN 5306-01-505-3631

Shear Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.